






Sealing Accessories




0605 Fluoropolymer Tape

	FKM		kg
<p>Can be used for temperatures from - 250°C to +260°C. Chemically inert and resistant to gases, acids, solvents, hydrocarbons, oils, alkalines, steam etc. Non-toxic, waterproof, self-lubricating. In accordance with CFR21. Can be used on all materials. Used to facilitate the preparation of leak-free threaded joints. Supplied on a reel, length = 12 m; width = 12.7 mm; thickness 0.08 mm.</p>			

0602 Captive Sealing Washer

	Technical polymer		G1 G2 K kg																																														
				<table border="1"> <thead> <tr> <th>C</th> <th></th> <th>G1</th> <th>G2</th> <th>K</th> <th>kg</th> </tr> </thead> <tbody> <tr> <td>M5x0.8</td> <td>0602 29 93 15</td> <td>5.2</td> <td>7.8</td> <td>1.5</td> <td>0.001</td> </tr> <tr> <td>G1/8</td> <td>0602 23 10 20</td> <td>10.3</td> <td>14</td> <td>2</td> <td>0.001</td> </tr> <tr> <td>G1/4</td> <td>0602 23 11 20</td> <td>13.7</td> <td>17.5</td> <td>2</td> <td>0.001</td> </tr> <tr> <td>G3/8</td> <td>0602 23 12 20</td> <td>17.2</td> <td>21</td> <td>2</td> <td>0.001</td> </tr> <tr> <td>G1/2</td> <td>0602 23 13 20</td> <td>21.5</td> <td>25.5</td> <td>2.5</td> <td>0.002</td> </tr> <tr> <td>G3/4</td> <td>0602 27 32 20</td> <td>27</td> <td>32</td> <td>2.5</td> <td>0.001</td> </tr> <tr> <td>G1</td> <td>0602 30 60 20</td> <td>33.8</td> <td>39</td> <td>3</td> <td>0.001</td> </tr> </tbody> </table>	C		G1	G2	K	kg	M5x0.8	0602 29 93 15	5.2	7.8	1.5	0.001	G1/8	0602 23 10 20	10.3	14	2	0.001	G1/4	0602 23 11 20	13.7	17.5	2	0.001	G3/8	0602 23 12 20	17.2	21	2	0.001	G1/2	0602 23 13 20	21.5	25.5	2.5	0.002	G3/4	0602 27 32 20	27	32	2.5	0.001	G1	0602 30 60 20	33.8
C		G1	G2	K	kg																																												
M5x0.8	0602 29 93 15	5.2	7.8	1.5	0.001																																												
G1/8	0602 23 10 20	10.3	14	2	0.001																																												
G1/4	0602 23 11 20	13.7	17.5	2	0.001																																												
G3/8	0602 23 12 20	17.2	21	2	0.001																																												
G1/2	0602 23 13 20	21.5	25.5	2.5	0.002																																												
G3/4	0602 27 32 20	27	32	2.5	0.001																																												
G1	0602 30 60 20	33.8	39	3	0.001																																												
<p>Maximum allowable working pressure: 20 bar</p>																																																	

0139 Bi-Material Captive Sealing Washer

	Zinc-plated steel with NBR seal		G K K1 kg																																								
				<table border="1"> <thead> <tr> <th>C</th> <th></th> <th>G</th> <th>K</th> <th>K1</th> <th>kg</th> </tr> </thead> <tbody> <tr> <td>G1/8</td> <td>0139 10 00</td> <td>14</td> <td>1</td> <td>1.7</td> <td>0.001</td> </tr> <tr> <td>G1/4</td> <td>0139 13 00</td> <td>17</td> <td>1</td> <td>1.7</td> <td>0.001</td> </tr> <tr> <td>G3/8</td> <td>0139 17 00</td> <td>22</td> <td>1.2</td> <td>2.1</td> <td>0.001</td> </tr> <tr> <td>G1/2</td> <td>0139 21 00</td> <td>26</td> <td>1.6</td> <td>2.5</td> <td>0.002</td> </tr> <tr> <td>G3/4</td> <td>0139 27 00</td> <td>32</td> <td>1.5</td> <td>2.5</td> <td>0.003</td> </tr> <tr> <td>G1</td> <td>0139 34 00</td> <td>39.6</td> <td>1.7</td> <td>2.6</td> <td>0.003</td> </tr> </tbody> </table>	C		G	K	K1	kg	G1/8	0139 10 00	14	1	1.7	0.001	G1/4	0139 13 00	17	1	1.7	0.001	G3/8	0139 17 00	22	1.2	2.1	0.001	G1/2	0139 21 00	26	1.6	2.5	0.002	G3/4	0139 27 00	32	1.5	2.5	0.003	G1	0139 34 00	39.6
C		G	K	K1	kg																																						
G1/8	0139 10 00	14	1	1.7	0.001																																						
G1/4	0139 13 00	17	1	1.7	0.001																																						
G3/8	0139 17 00	22	1.2	2.1	0.001																																						
G1/2	0139 21 00	26	1.6	2.5	0.002																																						
G3/4	0139 27 00	32	1.5	2.5	0.003																																						
G1	0139 34 00	39.6	1.7	2.6	0.003																																						
<p>Maximum allowable working pressure: 250 bar</p>																																											

Technical characteristics of captive seals 0602 Tightening torque			M5x0.8	G1/8	G1/4	G3/8	G1/2	G3/4	G1
		Min. Torque in daN.m	0.06	0.08	0.3	0.5	1	1.2	1.9
		Max. Torque daN.m	0.16	0.8	1.2	3	3.5	6	9