







# Brass Adaptors

## 0929 Equal 3-Piece Adaptor, Male BSPT Thread




	Brass, NBR 	<b>C</b>		<b>F</b>	<b>F1</b>	<b>L</b>	<b>L1</b>	<b>L2</b>	<b>kg</b>
		R1/8	<a href="#">0929 01 10</a>	15	5	27	9	8.5	0.017
		R1/4	<a href="#">0929 01 13</a>	19	6	33.5	11.5	9.5	0.035
		R3/8	<a href="#">0929 01 17</a>	22	8	36.5	13	10	0.054
		R1/2	<a href="#">0929 01 21</a>	27	12	45	15.5	12	0.088

This connection accessory makes assembly much easier thanks to its 3-piece design.  
 To join 2 threaded components, simply push together and tighten the sleeve nut, thus reducing installation time.  
 Maximum working pressure: 50 bar  
 Working temperature: -10° to +80°C  
 Supplied with seal

## 0123 Tailpiece Adaptor for Rubber Hose, Male BSPT Thread

	Brass 	<b>ØD</b>	<b>ØD1</b>	<b>C</b>		<b>F</b>	<b>L</b>	<b>L1</b>	<b>ØT</b>	<b>kg</b>
		4	6	R1/8	<a href="#">0123 04 10</a>	10	34	22.5	3.3	0.008
		6	8	R1/8	<a href="#">0123 06 10</a>	10	34	22.5	5	0.009
		7	9	R1/8	<a href="#">0123 07 10</a>	10	34	22.5	5	0.009
			9	R1/4	<a href="#">0123 07 13</a>	14	38.5	22.5	6	0.018
		10	9	R3/8	<a href="#">0123 07 17</a>	17	39	22.5	6	0.023
			12.2	R1/8	<a href="#">0123 10 10</a>	13	34	22.5	5	0.014
			12.2	R1/4	<a href="#">0123 10 13</a>	14	38.5	22.5	7	0.020
		12	12.2	R3/8	<a href="#">0123 10 17</a>	17	39	22.5	9.5	0.023
			14	R3/8	<a href="#">0123 12 17</a>	17	46	29.5	11	0.026
		13	15	R1/4	<a href="#">0123 13 13</a>	17	45.5	29.5	7	0.026
			15	R3/8	<a href="#">0123 13 17</a>	17	46	29.5	11	0.027
			15	R1/2	<a href="#">0123 13 21</a>	22	50.5	29.5	12	0.045
		16	18.5	R3/8	<a href="#">0123 16 17</a>	19	54.5	38	11	0.040
			18.5	R1/2	<a href="#">0123 16 21</a>	22	59	38	14	0.054
			18.5	R3/4	<a href="#">0123 16 27</a>	27	62	38	15	0.084
		19	21.5	R3/8	<a href="#">0123 19 17</a>	22	54.5	38	11	0.046
			21.5	R1/2	<a href="#">0123 19 21</a>	22	59	38	14	0.056
			21.5	R3/4	<a href="#">0123 19 27</a>	27	62	38	18	0.082
		25	26.7	R3/4	<a href="#">0123 25 27</a>	27	62	38	18	0.079
			27	R1	<a href="#">0123 25 34</a>	36	65	38	24	0.124
		32	34.5	R1	<a href="#">0123 32 34</a>	36	70	43	24	0.141

## 0136 Tailpiece Adaptor for Flexible Tubing, Male BSPT Thread

	Brass 	<b>ØD</b>	<b>ØD1</b>	<b>C</b>		<b>F</b>	<b>L</b>	<b>L1</b>	<b>ØT</b>	<b>kg</b>
		4	4.3	R1/8	<a href="#">0136 06 10</a>	10	26.5	15	2	0.007
			4.3	R1/4	<a href="#">0136 06 13</a>	14	31	15	2	0.015
			4.3	R3/8	<a href="#">0136 06 17</a>	17	31.5	15	2	0.020
		6	6.4	R1/8	<a href="#">0136 08 10</a>	10	26.5	15	4	0.007
			6.4	R1/4	<a href="#">0136 08 13</a>	14	31	15	4	0.015
		8	6.4	R3/8	<a href="#">0136 08 17</a>	17	31.5	15	4	0.020
			8.4	R1/4	<a href="#">0136 10 13</a>	14	31	15	6	0.016
			8.4	R3/8	<a href="#">0136 10 17</a>	17	31.5	15	6	0.020
		10	8.4	R1/2	<a href="#">0136 10 21</a>	22	36	15	6	0.039
			10.7	R1/4	<a href="#">0136 12 13</a>	14	36	20	7	0.018
			10.7	R3/8	<a href="#">0136 12 17</a>	17	36.5	20	8	0.023
		12	10.7	R1/2	<a href="#">0136 12 21</a>	22	41	20	8	0.041
			12.7	R1/4	<a href="#">0136 14 13</a>	14	36	20	7	0.019
			12.7	R3/8	<a href="#">0136 14 17</a>	17	36.5	20	10	0.023
			12.7	R1/2	<a href="#">0136 14 21</a>	22	41	20	10	0.040
			12.7	R3/4	<a href="#">0136 14 27</a>	27	44	20	10	0.071
		13	13.7	R3/8	<a href="#">0136 16 17</a>	17	36.5	20	11	0.023
			13.7	R1/2	<a href="#">0136 16 21</a>	22	41	20	11	0.041
		13.7	R3/4	<a href="#">0136 16 27</a>	27	44	20	11	0.070	