

# 441RH

## No-Skive Compact

Fire-retardant cover

### Primary Applications

General medium-pressure hydraulic and pneumatic systems as well as water and oil cooling circuits

### Type Approvals

Details please find on pages **Ab-16** to **Ab-19**

### Applicable Specifications

Parker Specification; Working pressure to SAE 100R2;  
Bend radius to SAE 100R16

### Construction

Inner tube: Synthetic rubber  
Reinforcement: One high-tensile steel wire braid  
Cover: Fire retardant synthetic rubber

Temperature Range ..... -40 °C up to +125 °C

Exception: Air ..... max. +70 °C  
Water ..... max. +85 °C



- **No-Skive** hose construction
- One wire braid construction – two wire braid performance
- +125 °C working temperature
- Fire-retardant cover
- Railway approved:
  - European Standard EN45545 HL2 for R22 (internal) and HL3 for R23 (external)
  - ISO 15540

### Recommended Fluids

Hydraulic fluids on a mineral-oil basis, water-glycol and lubricating oils, air and water. For air and gas applications with a pressure exceeding 1.7 MPa, the cover must be pin-pricked. Consult the chemical compatibility section on pages **Ab-26** to **Ab-34** for more detailed information.

### Fitting Series



| Part Number | Hose I.D. |      |      |      | Hose O.D.<br>mm | Pressure Rating              |      |                            |       | min. bend radius<br>mm | weight<br>kg |
|-------------|-----------|------|------|------|-----------------|------------------------------|------|----------------------------|-------|------------------------|--------------|
|             | DN        | Inch | Size | mm   |                 | max. working pressure<br>MPa | psi  | min. burst pressure<br>MPa | psi   |                        |              |
|             |           |      |      |      |                 |                              |      |                            |       |                        |              |
| 441RH-4     | 6         | 1/4  | -4   | 6.4  | 13.4            | 35.0                         | 5000 | 140.0                      | 20000 | 50                     | 0.27         |
| 441RH-5     | 8         | 5/16 | -5   | 7.9  | 15.0            | 29.7                         | 4250 | 118.8                      | 17000 | 55                     | 0.32         |
| 441RH-6     | 10        | 3/8  | -6   | 9.5  | 17.4            | 28.0                         | 4000 | 112.0                      | 16000 | 65                     | 0.42         |
| 441RH-8     | 12        | 1/2  | -8   | 12.7 | 20.7            | 24.5                         | 3500 | 98.0                       | 14000 | 90                     | 0.50         |
| 441RH-10    | 16        | 5/8  | -10  | 15.9 | 23.8            | 19.2                         | 2750 | 76.8                       | 11000 | 100                    | 0.65         |
| 441RH-12    | 19        | 3/4  | -12  | 19.1 | 27.8            | 15.7                         | 2250 | 62.8                       | 9000  | 120                    | 0.80         |
| 441RH-16    | 25        | 1    | -16  | 25.4 | 35.8            | 14.0                         | 2000 | 56.0                       | 8000  | 150                    | 1.22         |

The combination of high temperature and high pressure could reduce the hose life.

### Hose layline example

