

## Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

**Creation Date:** 17-12-2018

**Datasheet No:** DS421W

**Parker Part No:** 937068Q

**OEM:** Hydac

**OEM Part No:** 0280D003BN3HC

### Product Dimensions

<b>A (mm)</b>	69.0	<b>(inch)</b>	2.72
<b>B (mm)</b>	34.2	<b>(inch)</b>	1.35
<b>D (mm)</b>	69.0	<b>(inch)</b>	2.72
<b>E (mm)</b>	356.0	<b>(inch)</b>	14.02



### Construction Materials

<b>Seal(s):</b>	FPM: Fluoroelastomer
<b>Top Endcap:</b>	Mild steel tin plated
<b>Bottom Endcap:</b>	Mild steel tin plated
<b>Inner Support Cylinder:</b>	Mild steel tin plated
<b>Filter Media:</b>	Multilayer fibreglass with coated mesh on both sides

### Calculated Performance Criteria

**Differential Pressure ( $\Delta p$ ):** 0.00 bar @ 0 l/min  
**Tested to ISO3968 @ 32 cSt** 0.00 psi @ 0.00 gpm

**Efficiency:** >Beta 200 @ N/A microns & greater  
 >Beta 1000 @ 4.5 microns & greater

**Minimum Collapse Pressure:** >20 bar  
**Tested to ISO2941** >290 psi

**Dirt Holding Capacity acc. to ISO16889**  
 0.0 gram @ 0 bar terminal pressure drop  
 0.0 gram @ 0 psi terminal pressure drop