

Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date: 17-12-2018

Datasheet No: DS425W


Parker Part No: 937074Q

OEM: Hydac

OEM Part No: 0280D020BN3HC

Product Dimensions

A (mm)	69.0	(inch)	2.72
B (mm)	34.2	(inch)	1.35
D (mm)	69.0	(inch)	2.72
E (mm)	356.0	(inch)	14.02



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Mild steel tin plated
Bottom Endcap:	Mild steel tin plated
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (Δp): 0.00 bar @ 0 l/min
Tested to ISO3968 @ 32 cSt 0.00 psi @ 0.00 gpm

Efficiency: >Beta 200 @ 20 microns & greater
 >Beta 1000 @ 22 microns & greater

Minimum Collapse Pressure: >20 bar
Tested to ISO2941 >290 psi

Dirt Holding Capacity acc. to ISO16889
 0.0 gram @ 0 bar terminal pressure drop
 0.0 gram @ 0 psi terminal pressure drop