PAR�FIT[™]

Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	17-12-2018
Datasheet No:	DS1110W
Parker Part No:	938324Q
OEM:	MP Filtri
OEM Part No:	HP0371A25VN&AN

Product Dimensions

A (mm)	42.0	(inch)	1.65
B (mm)	22.8	(inch)	0.90
D (mm)	42.0	(inch)	1.65
E (mm)	90.0	(inch)	3.54





Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Mild steel tin plated
Bottom Endcap:	Mild steel tin plated
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (∆p):	0.57 bar @ 100 l/min		
Tested to ISO3968 @ 32 cSt	8.27 psi @ 22.00 gpm		
Efficiency: >Beta 200 @ 20 microns & greater >Beta 1000 @ 22 microns & greater			
Minimum Collapse Pressure:	: >20 bar		
Tested to ISO2941	>290 psi		
Dirt Holding Capacity acc. to ISO16889 >6.3 gram @ 7 bar terminal pressure drop >6.3 gram @ 102 psi terminal pressure drop			



ENGINEERING YOUR SUCCESS.

www.parker.com/parfit