# PAR�FIT<sup>™</sup>

## 

### Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	17-12-2018
Datasheet No:	DS1095W
Parker Part No:	938355Q
OEM:	MP Filtri
OEM Part No:	HP3201A10VN&AN

#### **Product Dimensions**

A (mm)	78.0	(inch)	3.07
B (mm)	40.5	(inch)	1.59
D (mm)	78.0	(inch)	3.07
E (mm)	115.0	(inch)	4.53



#### **Construction Materials**

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Mild steel tin plated
Bottom Endcap:	Mild steel tin plated
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

#### **Calculated Performance Criteria**

Differential Pressure (∆p):	0.45 bar @ 250 l/min		
Tested to ISO3968 @ 32 cSt	6.53 psi @ 54.99 gpm		
Efficiency: >Beta 200 @ 10 microns & greater >Beta 1000 @ 12 microns & greater			
Minimum Collapse Pressure:	: >20 bar		
Tested to ISO2941	>290 psi		
Dirt Holding Capacity acc. to ISO16889 >23.4 gram @ 7 bar terminal pressure drop >23.4 gram @ 102 psi terminal pressure drop			

### ENGINEERING YOUR SUCCESS.

www.parker.com/parfit