

Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date: 17-12-2018

Datasheet No: DS1033W



Parker Part No: 943733Q

OEM: MP Filtri

OEM Part No: MF4002A10HV&B

Product Dimensions

A (mm)	130.0	(inch)	5.12
C (mm)	64.5	(inch)	2.54
D (mm)	130.0	(inch)	5.12
E (mm)	204.0	(inch)	8.03



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Glass reinforced nylon
Bottom Endcap:	Glass reinforced nylon
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (Δp): 0.38 bar @ 600 l/min
Tested to ISO3968 @ 32 cSt 5.51 psi @ 131.98 gp

Efficiency: >Beta 200 @ 10 microns & greater
 >Beta 1000 @ 12 microns & greater

Minimum Collapse Pressure: >10 bar
Tested to ISO2941 >145 psi

Dirt Holding Capacity acc. to ISO16889
 >41.3 gram @ 4 bar terminal pressure drop
 >41.3 gram @ 58 psi terminal pressure drop