

## Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

**Creation Date:** 17-12-2018

**Datasheet No:** DS543W


**Parker Part No:** PR3087Q

**OEM:** Hydac

**OEM Part No:** 0110D010BN3HC

### Product Dimensions

<b>A (mm)</b>	47.0	<b>(inch)</b>	1.85
<b>B (mm)</b>	22.2	<b>(inch)</b>	0.87
<b>D (mm)</b>	47.0	<b>(inch)</b>	1.85
<b>E (mm)</b>	152.0	<b>(inch)</b>	5.98



### Construction Materials

<b>Seal(s):</b>	FPM: Fluoroelastomer
<b>Top Endcap:</b>	Mild steel tin plated
<b>Bottom Endcap:</b>	Mild steel tin plated
<b>Inner Support Cylinder:</b>	Mild steel tin plated
<b>Filter Media:</b>	Multilayer fibreglass with coated mesh on both sides

### Calculated Performance Criteria

<b>Differential Pressure (<math>\Delta p</math>):</b>	0.41 bar @ 60 l/min
<b>Tested to ISO3968 @ 32 cSt</b>	5.95 psi @ 13.20 gpm
<b>Efficiency:</b>	>Beta 200 @ 10 microns & greater >Beta 1000 @ 12 microns & greater
<b>Minimum Collapse Pressure:</b>	>20 bar
<b>Tested to ISO2941</b>	>290 psi
<b>Dirt Holding Capacity acc. to ISO16889</b>	6.4 gram @ 7 bar terminal pressure drop 6.4 gram @ 102 psi terminal pressure drop