



Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date: 17-12-2018

Datasheet No: DS139W


Parker Part No: PR3437Q

OEM: Pall

OEM Part No: HC9600FKS4H&Z

_				-	$\overline{}$				
ш	ra	~		∩t.	11	ime	ne	\sim	ne
г	ıv	u	u		ப		11.5	w	11.5

A (mm)	80.0	(inch)	3.15
B (mm)	43.2	(inch)	1.70
D (mm)	80.0	(inch)	3.15
E (mm)	116.0	(inch)	4.57





Construction Materials

Seal(s):	FPM: Fluoroelastomer		
Top Endcap:	Glass reinforced nylon		
Bottom Endcap:	Glass reinforced nylon		
Inner Support Cylinder:	Mild steel tin plated		
Filter Media:	Multilayer fibreglass with coated mesh on both sides		

Calculated Performance Criteria

Differential Pressure (\Delta p): 0.44 bar @ 100 l/min **Tested to ISO3968 @ 32 cSt** 6.38 psi @ 22.00 gpm

Efficiency: >Beta 200 @ 10 microns & greater

>Beta 1000 @ 12 microns & greater

Minimum Collapse Pressure: >20 bar Tested to ISO2941 >290 psi

Dirt Holding Capacity acc. to ISO16889

>25.0 gram @ 7 bar terminal pressure drop >25.0 gram @ 102 psi terminal pressure drop

