


G4MX Female connector

Triple-Lok® 37° Flare end / Female BSPP thread (ISO 1179-1)



| Tube O.D. mm | in. | Thread BSPP T4 | Thread UN/UNF-2A T | C1 mm | D mm | L2 mm | Weight (steel) g/1 piece | Triple-Lok® Steel | Triple-Lok® Stainless Steel | PN (bar) | |
|--------------------|-------|----------------------|--------------------------|----------|---------|----------|--------------------------------|----------------------|--------------------------------|----------|-----|
| | | | | | | | | | | S | SS |
| 6 | 1/4 | 1/8-28 | 7/16-20 | 17 | 4 | 30 | 15 | 4G4MXS | 4G4MXSS | 315 | 315 |
| 6 | 1/4 | 1/4-19 | 7/16-20 | 19 | 4 | 35 | 42 | 4-4G4MXS | 4-4G4MXSS | 400 | 350 |
| 8 | 5/16 | 1/8-28 | 1/2-20 | 17 | 6 | 30 | 22 | 5G4MXS | 5G4MXSS | 315 | 315 |
| 8 | 5/16 | 1/4-19 | 1/2-20 | 19 | 6 | 35 | 40 | 5-4G4MXS | 5-4G4MXSS | 400 | 350 |
| 10 | 3/8 | 1/4-19 | 9/16-18 | 19 | 8 | 36 | 40 | 6G4MXS | 6G4MXSS | 400 | 350 |
| 10 | 3/8 | 3/8-19 | 9/16-18 | 22 | 8 | 37 | 50 | 6-6G4MXS | 6-6G4MXSS | 350 | 350 |
| 12 | 1/2 | 3/8-19 | 3/4-16 | 22 | 10 | 40 | 64 | 8G4MXS | 8G4MXSS | 350 | 350 |
| 12 | 1/2 | 1/2-14 | 3/4-16 | 30 | 10 | 46 | 116 | 8-8G4MXS | 8-8G4MXSS | 400 | 350 |
| 14, 15, 16 | 5/8 | 1/2-14 | 7/8-14 | 30 | 12 | 48 | 121 | 10G4MXS | 10G4MXSS | 350 | 350 |
| 18, 20 | 3/4 | 3/4-14 | 1 1/16-12 | 36 | 16 | 52 | 188 | 12G4MXS | 12G4MXSS | 315 | 315 |
| 25 | 1 | 1 1/11 | 1 5/16-12 | 46 | 22 | 60 | 340 | 16G4MXS | 16G4MXSS | 280 | 280 |
| 28, 30, 32 | 1 1/4 | 1 1/4-11 | 1 5/8-12 | 50 | 28 | 63 | 438 | 20G4MXS | 20G4MXSS | 210 | 210 |
| 35, 38 | 1 1/2 | 1 1/2-11 | 1 7/8-12 | 55 | 33 | 67 | 526 | 24G4MXS | 24G4MXSS | 140 | 140 |

Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$$

Pressure ratings – PN shown, apply to Steel and Stainless Steel versions of the product.

