


VKA Blanking plug for cones

EO 24° DKO swivel



X1) O-ring OR

| Series | D1 | L1 | Weight g/1 piece | Order code* | PN (bar) ¹⁾ | | |
|-----------------|--------|------|---------------------|--------------|------------------------|-----|-----|
| | | | | | CF | 71 | MS |
| L ³⁾ | 06 | 18.5 | 6 | VKA06 | 500 | 315 | 200 |
| | 08 | 18.5 | 9 | VKA08 | 500 | 315 | 200 |
| | 10 | 20.0 | 15 | VKA10 | 500 | 315 | 200 |
| | 12 | 20.5 | 21 | VKA12 | 400 | 315 | 200 |
| | 15 | 20.5 | 32 | VKA15 | 400 | 315 | 200 |
| | 18 | 22.5 | 49 | VKA18 | 400 | 315 | 200 |
| | 22 | 25.0 | 80 | VKA22 | 250 | 160 | 100 |
| | 28 | 25.5 | 131 | VKA28 | 250 | 160 | 100 |
| | 35 | 30.0 | 240 | VKA35 | 250 | 160 | 100 |
| | 42 | 30.0 | 343 | VKA42 | 250 | 160 | 100 |
| S ⁴⁾ | 06 | 18.5 | 6 | VKA06 | 800 | 630 | 400 |
| | 08 | 18.5 | 9 | VKA08 | 800 | 630 | 400 |
| | 10 | 20.0 | 15 | VKA10 | 800 | 630 | 400 |
| | 12 | 20.5 | 21 | VKA12 | 630 | 630 | 400 |
| | 14 | 22.5 | 30 | VKA14 | 630 | 630 | 400 |
| | 16 | 23.5 | 40 | VKA16 | 630 | 400 | 250 |
| | 20 | 28.5 | 78 | VKA20 | 420 | 400 | 250 |
| | 25 | 29.0 | 120 | VKA25 | 420 | 400 | 250 |
| | 30 | 30.5 | 180 | VKA30 | 420 | 400 | 250 |
| | 38 | 33.0 | 309 | VKA38 | 420 | 315 | 200 |

1) Pressure shown = item deliverable

3) L = light series; 4) S = heavy series

$$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$$

Information on ordering alternative sealing materials see page 17.

 *Please add the **suffixes** below according to the material/surface required.

| Order code suffixes | | | |
|---------------------------------|-----------------------------|---------|---|
| Material | Suffix surface and material | Example | Standard sealing material (no additional suffix needed) |
| Steel, zinc plated, Cr(VI)-free | CF | VKA16CF | NBR |
| Stainless Steel | 71 | VKA1671 | VIT |
| Brass | MS | VKA16MS | NBR |